



**GOLD SUPER 4T PLUS 10W-30** is suitable for use in many older vehicles and a few late model cars and trucks, often those with larger 6-cylinder and V-8 and/or high performance engines. SAE 10W-30 is also designated as a Resource Conserving lubricant by API.

**Properties:-**

- Prolong engine life
- Clean engines and positive crankcase ventilation systems resulting in minimal deposits under heavy load and stop-and-go driving conditions.
- Superior soot control and acid neutralization.
- Protects against wear and corrosion
- Superior thermal and oxidation stability
- Reduce friction, sludge and varnish

Specification & Characteristics	<b>GOLD SUPER 4T PLUS 10W-30</b>		
	<b>Test Properties</b>	<b>Test Method</b>	<b>SPECIFICATION</b>
	<b>API SERVICE CATEGORY</b>		<b>SM</b>
	<b>SAE GRADE</b>		<b>10W-30</b>
	Appearance	Visual	Bright & Clear
	Colour	ASTM D 1500	Natural
	Density @ 29.5, °C, g/ml	ASTM D 1298	0.840 Min
	Viscosity, Kinematic 100 at°C, cSt	ASTM D 445	10 - 12
	Viscosity Index	ASTM D 2270	110 Min
	Pour Point, °C	ASTM D 97	-21 Max
	Flash Point, COC, °C	ASTM D 92	200 Min
	TBN, mg KOH/g	ASTM D 2896	6.0 Min

**Packaging Options:** GOLD SUPER 4T PLUS 10W-30 is offered in 01, 26, 50 & 210 Liters.

**Health & Safety:** See corresponding product MSDS

The information contained herein is, to our best knowledge, true and accurate, but all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control. There is no implied warranty of merchantability or fitness for purpose of the product or products described herein. In submitting this information, no liability is assumed or license or other rights express or implied given with respect to any existing or pending patent, patent applications or trademarks. The observance of all legal regulations and patents is the responsibility of the user.