



GOLD SYN FLUID PLUS

(Chain Oil)

GOLD SYN FLUID PLUS oils are blended with synthetic base oil and plural high refined additives such as anti-oxidizer, anti-wear agent, anti corrosion agent and so on. It is particularly suitable for highly specialized applications where oil fling and drip need to be avoided e.g. chains, overhead tracks, and hinges. GOLD SYN FLUID PLUS is recommended as a chain link lubricant. In these and similar difficult to lubricate pin and joint applications its anti-wear and long life characteristics will provide continuous effective lubrication with minimum consumption.

PROPERTIES

- Excellent antiwear properties & Good oxidation stability
- Low volatility & High Flash Point
- Improved lubrication can result in reduced energy consumption
- Excellent lubrication and prevent wear and corrosion of bearing under all operating conditions.
- Good compatibility with sealing materials.

GOLD SYN FLUID PLUS			
	Test Properties	Test Method	Specification
Typical Properties & Characteristics	Colour	ASTM D 1500	0.5 Max
	Density @ 29.5, °C, g/ml	ASTM D 1298	0.82 Min
	Viscosity, Kinematic 40 at°C, cSt	ASTM D 445	260 - 300
	Viscosity Index	ASTM D 2270	140 Min
	Pour Point, °C	ASTM D 97	-30 Max
	Flash Point, COC, °C	ASTM D 92	260 Min
	Fire Point, COC, °C	ASTM D 92	300 Min
	Rust Test, 48 hrs. Synthetic	ASTM D 130	To Pass
	Operating temperatures °C	Internal	-18°C – 250°C

Packaging Options: GOLD SYN FLUID PLUS is offered in 5, 26, 50 & 210 Liter.

Health & Safety: See corresponding product MSDS

The information contained herein is, to our best knowledge, true and accurate, but all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control. There is no implied warranty of merchantability or fitness for purpose of the product or products described herein. In submitting this information, no liability is assumed or license or other rights express or implied given with respect to any existing or pending patent, patent applications or trademarks. The observance of all legal regulations and patents is the responsibility of the user.

GOC Petrochemicals Pvt. Ltd.

Regd. Office / Factory Address: Plot No. 5, Survey No. 207/5, Village Umalkui, Silvassa - 396 230 (U.T. of D. & N.H.)

+91 99 798 54 133 gold@goldoilcorporation.com www.goldoilcorporation.com