An ISO 9001:2015 Certified Company

GOLD MAGIC PLUS 15W 40 API CI-4 PLUS

(High Speed Diesel Engine Oil)

GOLD MAGIC PLUS 15W 40 CI-4 PLUS is formulated by highly saturated base oil & special type additives. It is protect heart of engine by avoiding & protecting engine by wear & corrosion, controls engine deposits, resist oil thickening & reduces oil consumption to offer extended engine life.

GOLD MAGIC PLUS 15W40 is formulated to exceed API's latest specifications: Diesel engine oil specifications: CI-4 Plus.

Properties

- Prolong engine life
- > Superior soot control and acid neutralization.
- > Protects against wear and corrosion
- > Superior thermal and oxidation stability
- > Reduce friction, sludge and varnish
- > Reduce piston deposits, cylinder wear and fuel consumption.

	GOLD MAGIC PLUS 15W 40		
	Test Properties	Test Method	SPECFICATION
	API SERVICE CATEGORY		CI-4 PLUS
	SAE GRADE		15W-40
Specification & Characteristics	Appearance	Visual	Bright & Clear
	Colour	ASTM D 1500	Natural
	Density @ 29.5, °C, g/ml	ASTM D 1298	0.850 Min
	Viscosity, Kinematic 100 at °C, cSt	ASTM D 445	14 - 16
	Viscosity Index	ASTM D 2270	120 Min
	Pour Point, °C	ASTM D 97	-15 Max
	Flash Point, COC, °C	ASTM D 92	220 Min
	TBN, mg KOH/g	ASTM D 2896	12.0 Min

Packaging Options: GOLD MAGIC PLUS 15W 40 CI-4 PLUS is offered in 3, 26, 50 & 210 Liters. Health & Safety: See corresponding product MSDS

The information contained herein is, to our best knowledge, true and accurate, but all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control. There is no implied warranty of merchantability or fitness for purpose of the product or products described herein. In submitting this information, no liability is assumed or license or other rights express or implied given with respect to any existing or pending patent, patent applications or trademarks. The observance of all legal regulations and patents is the responsibility of the user.

GOC Petrochemicals Pvt. Ltd.