An ISO 9001:2015 Certified Company

GOLD UTTO

GOLD UTTO is Extra High Performance Diesel Engine oil specially developed for enhanced wear protection, superior corrosion protection and low emission for tractor. Gold UTTO is provides improved protection against wear and deposits and is suitable for use in wide range of on and off-highway applications where such type of lubricant is recommended.

Properties

- > Better detergency reduces deposits and keep the engines cleaner
- > Superior soot control and acid neutralization.
- > Good corrosion inhibition properties provide Protection against wear and corrosion.
- Superior thermal and oxidation stability
- > Reduce friction, sludge and varnish
- > Prolong engine life

	GOLD UTTO		
	Test Properties	Test Method	SPECFICATION
	API SERVICE CATEGORY		GL-4
	SAE GRADE		10W30
Specification & Characteristics	Appearance	Visual	Bright & Clear
	Colour	ASTM D 1500	Natural
	Density @ 29.5, °C, g/ml	ASTM D 1298	0.860 Min
	Viscosity, Kinematic 100 at°C, cSt	ASTM D 445	10 - 12
	Viscosity Index	ASTM D 2270	120 Min
	Pour Point, °C	ASTM D 97	-12 Max
	Flash Point, COC, °C	ASTM D 92	220 Min

Packaging Options: GOLD UTTO is offered in 1, 5, 7.5, 10, 15, 20, 26, 50 & 210 Liters.

Health & Safety: See corresponding product MSDS

The information contained herein is, to our best knowledge, true and accurate, but all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control. There is no implied warranty of merchantability or fitness for purpose of the product or products described herein. In submitting this information, no liability is assumed or license or other rights express or implied given with respect to any existing or pending patent, patent applications or trademarks. The observance of all legal regulations and patents is the responsibility of the user.