



## GOLD ATF-A

### (Automatic Transmission Fluid Oil)

**GOLD ATF-A** is formulated with high quality paraffinic base stocks, detergents, dispersants, oxidation and corrosion inhibitors, antiwear and antifoam additive. ATF-A may be used for automatic and semiautomatic gearboxes, power-steering and other equipment for which an ATF –A type mineral oil fluid is recommended.

#### Properties

- Very high and stable Viscosity
- Very low Pour Point
- Good stability
- Specific friction properties

	GOLD ATF		
	Test Properties	Test Method	TYPE A
Specification & Characteristics	Appearance	Visual	Bright & Clear
	Colour	ASTM D 1500	Std. Red
	Density @ 29.5, °C, g/ml	ASTM D 1298	0.84 Min
	Viscosity, Kinematic 100 at °C, cSt	ASTM D 445	6 - 7
	Viscosity Index	ASTM D 2270	125 Min
	Pour Point, °C	ASTM D 97	-33 Max
	Flash Point, COC, °C	ASTM D 92	180 Min

**Packaging Options:** GOLD ATF-A series is offered in 1, 5, 26, 50 & 210 Liters.

**Health & Safety:** See corresponding product MSDS

The information contained herein is, to our best knowledge, true and accurate, but all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control. There is no implied warranty of merchantability or fitness for purpose of the product or products described herein. In submitting this information, no liability is assumed or license or other rights express or implied given with respect to any existing or pending patent, patent applications or trademarks. The observance of all legal regulations and patents is the responsibility of the user.