



GOLD G.E.C. 30, 40 & 50

GOLD G.E.C. is formulated with high quality paraffinic base stocks, detergents, dispersants, oxidation and corrosion inhibitors, antiwear and antifoam additive. The resulting oils meet or exceed the requirements of API Service Classification CC and SE and U.S. Military specification MIL-L-2104B. It also meets the B.I.S specification, IS 13656, EDL-2.

Properties:

- Effective antiwear characteristics protect engine components
- Good detergency characteristics ensure cleaner engine
- Better corrosion inhibition properties offer protection against rust and corrosion

GOLD G.E.C.					
Test Properties		Test Method	Grade		
SAE			30	40	50
API			CC, CD / SE	CC, CD / SE	CC, CD / SE
Specification & Characteristics	Appearance	Visual	Bright & Clear	Bright & Clear	Bright & Clear
	Colour	ASTM D 1500	Natural	Natural	Natural
	Density @ 29.5, °C, g/ml	ASTM D 1298	0.84 Min	0.84 Min	0.84 Min
	Viscosity, Kinematic 100 at°C, cSt	ASTM D 445	10.5 – 12.5	14 - 15	16 - 18
	Viscosity Index	ASTM D 2270	95 Min	95 Min	100 Min
	Pour Point, °C	ASTM D 97	-6 Max	-6 Max	-6 Max
	Flash Point, COC, °C	ASTM D 92	190 Min	210 Min	220 Min
	TBN, mg KOH/g	ASTM D 2896	3.0 Min	3.0 Min	3.0 Min

Packaging Options: GOLD G.E.C. is offered in 26, 50 & 210 Liters.

Health & Safety: See corresponding product MSDS

The information contained herein is, to our best knowledge, true and accurate, but all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control. There is no implied warranty of merchantability or fitness for purpose of the product or products described herein. In submitting this information, no liability is assumed or license or other rights express or implied given with respect to any existing or pending patent, patent applications or trademarks. The observance of all legal regulations and patents is the responsibility of the user.