



GOLD SUPER 4T PLUS 20W-40 API SM GRADE

GOLD SUPER 4T PLUS, SAE 20W-40 is a superior quality motor cycle oil engineered to enhance the power and performance of all the new age two-wheelers; meeting API SM, JASO T 903 MA-2 requirements. It provides longer engine life, smooth clutch operation and maximum gear & wears protection.

Properties

- Possess special frictional properties required for smooth operation of wet clutches used in 4 stroke 2 wheelers
- Provide outstanding oxidation stability there by ensuring cleaner engine and extended oil life
- Good wear protection
- Minimize engine deposits due to excellent sludge and varnish control

GOLD SUPER 4T PLUS			
	Test Properties	Test Method	Specification
	API Grade		SM
	SAE Grade		20W-40
Specification & Characteristics	Appearance	Visual	Bright & Clear
	Colour	ASTM D 1500	Red
	Density @ 29.5, °C, g/ml	ASTM D 1298	0.85 Min
	Viscosity, Kinematic 100 at°C, cSt	ASTM D 445	14 - 16
	Viscosity Index	ASTM D 2270	120 Min
	Pour Point, °C	ASTM D 97	-12 Max
	Flash Point, COC, °C	ASTM D 92	210 Min
	TBN, mg KOH/g	ASTM D 2896	5.0 Min

Packaging Options: GOLD SUPER 4T PLUS 20W-40 is offered in 0.9, 1, 20, 26, 50 & 210 Liters.

Health & Safety: See corresponding product MSDS

The information contained herein is, to our best knowledge, true and accurate, but all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control. There is no implied warranty of merchantability or fitness for purpose of the product or products described herein. In submitting this information, no liability is assumed or license or other rights express or implied given with respect to any existing or pending patent, patent applications or trademarks. The observance of all legal regulations and patents is the responsibility of the user.