

**GOLD ROTO SPIN 2, 5, 10, 12, 15 & 22**

**GOLD ROTO SPIN** series oils are range of high quality spindle lubricants for use on modern textile machines. Manufactured from the highest quality base stocks and ashless additives, it reduces spindle wear, protects against rust and may be easily removed by washing textile contamination occurs.

**PROPERTIES**

- Good oxidation stability and ageing resistance
- Rapid air release and low foaming
- Excellent corrosion protection for steel and non ferrous metals
- Easy removal of textile contamination by washing
- Easy start-up and minimum power loss.
- Low viscosity R & O type lubricants are specified

|   | <i>Test Properties</i>            | <i>Test Method</i> | GOLD ROTO SPIN series |                 |                  |                  |                  |                  |
|---|-----------------------------------|--------------------|-----------------------|-----------------|------------------|------------------|------------------|------------------|
|   |                                   |                    | <i>ISO VG 2</i>       | <i>ISO VG 5</i> | <i>ISO VG 10</i> | <i>ISO VG 12</i> | <i>ISO VG 15</i> | <i>ISO VG 22</i> |
| <b>Typical Properties &amp; Characteristics</b> | Appearance                        | Visual             | Bright & Clear        | Bright & Clear  | Bright & Clear   | Bright & Clear   | Bright & Clear   | Bright & Clear   |
|   | Colour                            | ASTM D 1500        | 1.0 Max               | 1.0 Max         | 1.0 Max          | 1.0 Max          | 1.0 Max          | 1.0 Max          |
|   | Density @ 29.5, °C, g/ml          | ASTM D 1298        | 0.75 Min              | 0.80 Min        | 0.81 Min         | 0.82 Min         | 0.82 Min         | 0.82 Min         |
|   | Viscosity, Kinematic 40 at°C, cSt | ASTM D 445         | 2 Typ.                | 4 - 6           | 8 - 12           | 10 - 14          | 14 - 16          | 20 - 24          |
|   | Pour Point, °C                    | ASTM D 97          | -21 Max               | -21 Max         | -21 Max          | -21 Max          | -15 Max          | -15 Max          |
|   | Flash Point, COC, °C              | ASTM D 92          | 100 Min               | 120 Min         | 170 Min          | 170 Min          | 180 Min          | 180 Min          |

**Packaging Options:** **GOLD ROTO SPIN SERIES** is offered in 26, 50 & 210 Liter.

**Health & Safety:** Material Safety Data Sheet can be provided on request

The information contained herein is, to our best knowledge, true and accurate, but all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control. There is no implied warranty of merchantability or fitness for purpose of the product or products described herein. In submitting this information, no liability is assumed or license or other rights express or implied given with respect to any existing or pending patent, patent applications or trademarks. The observance of all legal regulations and patents is the responsibility of the user.