



## GOLD CANE-CRUSH 40, 60, 90

(Sugar mill Oils)

**GOLD CANE-CRUSH** series oils are manufactured from high refined base oils, special compounding agents and select non toxic EP additives, providing excellent anti-wear and anti corrosion properties. This is recommended for mill-roll bearings of sugar mills. Also suitable for centralized lubrication system of slow speed spur and helical gears.

### PROPERTIES:-

- Good oxidation stability and ageing resistance.
- Rapid air release and low foaming.
- Excellent lubrication and prevent wear and corrosion of bearing under all operating conditions.
- Good compatibility with sealing materials.

		<b>GOLD CANE-CRUSH SERIES</b>				
		<i>Test Properties</i>	<i>Test Method</i>	<i>40</i>	<i>60</i>	<i>90</i>
<b>Properties &amp; Characteristics</b>	Colour		ASTM D 1298	Black	Black	Black
	Viscosity, Kinematic 100 at°C, cSt		ASTM D 445	37 - 43	57 - 63	86 - 94
	Flash Point, COC, °C, Min		ASTM D 92	200	200	200

**Packaging Options:** - GOLD CANE-CRUSH series is offered in 26, 50 & 210 Liter.

**Health & Safety:** See corresponding product MSDS

The information contained herein is, to our best knowledge, true and accurate, but all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control. There is no implied warranty of merchantability or fitness for purpose of the product or products described herein. In submitting this information, no liability is assumed or license or other rights express or implied given with respect to any existing or pending patent, patent applications or trademarks. The observance of all legal regulations and patents is the responsibility of the user.