



GOLD THERMIC OIL M

(Heat Transfer Oil)

GOLD THERMIC OIL M is based on carefully selected highly refined oils chosen for its ability to provide superior performance in indirect closed fluid heat transfer systems. Gold Thermic oils M can be used up to a bulk oil temperature of 350°C and will stand skin temperature up to 350°C(662°F) to 380°C (716°F). Gold Super Thermic Oil has high specific heat and thermal conductivity at all temperatures and, therefore, will give rapid heating and flexibility in a system.

PROPERTIES:-

- Operating temperature range from -15°C to + 380°C.
- Excellent resistance to Thermal cracking and chemical oxidation
- Good oxidation stability and High thermal stability
- Excellent corrosion protection
- Non-toxic
- Good compatibility with sealing materials

GOLD THERMIC OIL M			
	<i>Test Properties</i>	<i>Test Method</i>	<i>Specification</i>
Typical Properties & Characteristics	Appearance	Visual	Bright & Clear
	Colour	ASTM D 1500	3.5 Max
	Density @ 29.5, °C, g/ml	ASTM D 1298	0.820 Min
	Viscosity, Kinematic 40 at°C, cSt	ASTM D 445	27 - 36
	Flash Point, COC, °C	ASTM D 92	190 Min
	Pour Point, COC, °C	ASTM D 97	-12 Max

Packaging Options: GOLD THERMIC OIL M is offered in 26, 50 & 210 Liter.

Health & Safety: See corresponding product MSDS

The information contained herein is, to our best knowledge, true and accurate, but all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control. There is no implied warranty of merchantability or fitness for purpose of the product or products described herein. In submitting this information, no liability is assumed or license or other rights express or implied given with respect to any existing or pending patent, patent applications or trademarks. The observance of all legal regulations and patents is the responsibility of the user.