



## GOLD 472

(Warping Oil)

**GOLD 472** is specially compounded emulsifying Warping oil composed of petroleum oil and special emulsifiers. It mixes readily with hot or cold water. It forms homogenous and exceptionally stable emulsions, which show no apparent separation after long period of use or storage.

### PROPERTIES:-

- High performance
- Uniform frictional attributes
- It is a highly washable and high antistatic lubricant which gives stable emulsion with water.
- Due to its good emulsifying effect, it can easily be removed by washing.
- Proper lubrication

GOLD 472			
	<i>Test Properties</i>	<i>Test Method</i>	<i>Specification</i>
Specification Properties & Characteristics	Appearance	Visual	Bright & Clear
	Colour, Max	ASTM D 1500	1.0
	Density @ 29.5, °C, g/ml, Min	ASTM D 1298	0.830
	Viscosity, Kinematic at 40°C, cSt, Min	ASTM D 445	14
	Flash Point, COC, °C, Min	ASTM D 92	150
	Emulsion test	Internal	Should Passes
	pH of 5% solution	Internal	6 – 8
	Copper Corrosion @100°C	ASTM D 130	1b

**Packaging Options:** GOLD 472 is offered in 26, 50 & 210 Liter.

**Health & Safety:** See corresponding product MSDS

The information contained herein is, to our best knowledge, true and accurate, but all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control. There is no implied warranty of merchantability or fitness for purpose of the product or products described herein. In submitting this information, no liability is assumed or license or other rights express or implied given with respect to any existing or pending patent, patent applications or trademarks. The observance of all legal regulations and patents is the responsibility of the user.