

GOLD G.E.C. 20W-40

(Heavy Duty Engine Oil)

GOLD GEC 20W-40 is formulated with high quality paraffinic base stocks, detergents, dispersants, oxidation and corrosion inhibitors, antiwear and antifoam additive. The resulting oils meet or exceed the requirements of API Service Classification CF and SF and BIS specification, IS 13656-2002, EDL-2/EPL 2.

Properties

- > Effective antiwear characteristics protect engine components
- > Good detergency characteristics ensure cleaner engine
- > Better corrosion inhibition properties offer protection against rust and corrosion

	GOLD GEC 20W-40		
Т	TEST PROPERTIES	TEST METHOD	SPECIFICATION
A	API GRADE		CF/SF
S	SAE GRADE		20W-40
A	Appearance	Visual	Bright & Clear
Characteristics	Colour	ASTM D 1500	Std. Red
racte	Density @ 29.5, °C, g/ml	ASTM D 1298	0.85 Min
-	/iscosity, Kinematic 100 at°C, cSt	ASTM D 445	14 - 15
on &	/iscosity Index	ASTM D 2270	100 Min
Specification	Pour Point, °C	ASTM D 97	-6 Max
Decif	Flash Point, COC, °C	ASTM D 92	210 Min
Σ	ГВN, mg KOH/g	ASTM D 2896	4.0 Min

Packaging Options: GOLD GEC 20W-40 series is offered in 7.5, 10, 15, 20, 26, 50 & 210 Liters.

Health & Safety: See corresponding product MSDS

The information contained herein is, to our best knowledge, true and accurate, but all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control. There is no implied warranty of merchantability or fitness for purpose of the product or products described herein. In submitting this information, no liability is assumed or license or other rights express or implied given with respect to any existing or pending patent, patent applications or trademarks. The observance of all legal regulations and patents is the responsibility of the user.

GOC Petrochemicals Pvt. Ltd.

Regd. Office / Factory Address: Plot No. 5, Survey No. 207/5, Village Umarkui, Silvassa - 396 230 (U.T. of D. & N.H.) +91 99 798 54 133 gold@goldoilcorporation.com
www.goldoilcorporation.com