



## GOLD SUPER QUENCHING OIL

**GOLD SUPER QUENCHING OIL** is general purpose straight mineral Quenching Oils manufactured from selected crudes of paraffin type. These grade are refined by an exclusive finishing process –an advance hydrogen refining process which enhances the higher resistance to oxidation, long service life and low carbon residue of these quenching oil Meets the requirement of IS 2664 -1980, Straight mineral Oils. These series are given below:-

**GOLD SUPER QUENCHING OIL** - It is use for low quenching.

### PROPERTIES:-

- Good thermal properties
- Good chemical and oxidation stability
- High boiling points and low volatility
- High flash and fire points
- Good compatibility with sealing materials

	<i>Test Properties</i>	<i>Test Method</i>	<b>Specification</b>
<b>Characteristics</b>	Appearance	Visual	Bright & Clear
	Colour, Max	ASTM D 1500	4.5
	Viscosity, Kinematic 40 at°C, cSt	ASTM D 445	28 - 36
	Flash Point, COC, °C, Min	ASTM D 92	180
	Fire Point, COC, °C, Min	ASTM D 92	186

**Packaging Options:** GOLD SUPER QUENCHING OIL is offered in 26, 50 & 210 Liter.

**Health & Safety:** See corresponding product MSDS

The information contained herein is, to our best knowledge, true and accurate, but all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control. There is no implied warranty of merchantability or fitness for purpose of the product or products described herein. In submitting this information, no liability is assumed or license or other rights express or implied given with respect to any existing or pending patent, patent applications or trademarks. The observance of all legal regulations and patents is the responsibility of the user.