

**GOLD DW RUST OIL**

(Solvent Base Rust preventive)

GOLD DW RUST OIL Dewatering fluids are mainly based on hydrocarbon solvents containing a selected combination of additives that enable complete water displacement and penetration of treated metal surfaces. After removing the metal from the solution, the solvent evaporates leaving a clean, dry surface.

PROPERTIES:-

- Good oxidation stability and ageing resistance
- Rapid air release and low foaming
- Excellent corrosion protection.
- Avoids water spots when dewatering sensitive surfaces, such as polished or plated components.
- Good compatibility with sealing materials

GOLD DW RUST OIL			
	Test Properties	Test Method	DW RUST OIL
Specification Properties & Characteristics	Appearance	Visual	Bright & Clear
	Colour	ASTM D 1500	Brown
	Density @ 29.5, °C, g/ml	ASTM D 1298	0.800 Min
	Viscosity, Kinematic 40 at°C, cSt	ASTM D 445	1.5 Min
	Flash Point, COC, °C	ASTM D 92	50 Min
	DEMULSIBILITY TEST	ASTM D 1401	PASS
	FILM THICKNESS	-	2 micron
	COVERAGE, Sq. meter / Ltr	-	64
	FILM TYPE	-	OILY & TACKY
	COPPER STRIP CORROSION 3Hrs.	ASTM D 130	1
	EVAPORATION LOSS @110°C FOR 03 HRS.	ASTM D 5800	Report

Packaging Options: Gold Rustol Sol series is offered in 26, 50 & 210 Liter.

Health & Safety: See corresponding product MSDS

The information contained herein is, to our best knowledge, true and accurate, but all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control. There is no implied warranty of merchantability or fitness for purpose of the product or products described herein. In submitting this information, no liability is assumed or license or other rights express or implied given with respect to any existing or pending patent, patent applications or trademarks. The observance of all legal regulations and patents is the responsibility of the user.