

**GOLD PERFORMANCE RUSTOL 175**

(De-Watering Rust Preventive)

GOLD PERFORMANCE RUSTOL 175 is a soft film; solvent deposited water displacing type, corrosion preventives. These are mainly based on hydrocarbon solvents containing a selected combination of additives that enable complete water displacement and penetration of treated metal surfaces. After removing the metal from the solution, the solvent evaporates leaving a clean, dry surface. Gold Performance Rustol 175 complies to IS: 1154 Specifications.

PROPERTIES:

- Excellent corrosion protection for machine tools and components.
- Avoids water spots when dewatering sensitive surfaces, such as polished or plated components.
- Good oxidation stability and ageing resistance
- Rapid air release and low foaming
- Good compatibility with sealing materials

GOLD PERFORMANCE RUSTOL 175			
	Test Properties	Test Method	Specification
Specification Properties & Characteristics	Appearance	Visual	Bright & Clear
	Colour	ASTM D 1500	Brown
	Density @ 29.5, °C, g/ml	ASTM D 1298	0.78 Min
	Viscosity, Kinematic 40 at°C, cSt	ASTM D 445	2.0 Typ.
	Flash Point, COC, °C	ASTM D 92	40 Min
	Demulsibility Test	ASTM D 1401	PASS
	Film Thickness	-	4 - 5
	Coverage, Sq. meter / Ltr	-	30 - 50
	Film Type	-	OILY & TACKY
	Copper Strip Corrosion 3Hrs.	ASTM D 130	1
	Humidity cabinet test, h, Min	ASTM D 1748	360
	Corrosion Protection, Indoor area, Month Outdoor area, Month	-	6 - 9 1 - 3

Packaging Options: Gold Performance Rustol 175 is offered in 26, 50 & 210 Liter.

Health & Safety: See corresponding product MSDS

The information contained herein is, to our best knowledge, true and accurate, but all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control. There is no implied warranty of merchantability or fitness for purpose of the product or products described herein. In submitting this information, no liability is assumed or license or other rights express or implied given with respect to any existing or pending patent, patent applications or trademarks. The observance of all legal regulations and patents is the responsibility of the user.

GOC Petrochemicals Pvt. Ltd.

Regd. Office / Factory Address: Plot No. 5, Survey No. 207/5, Village Umarkui, Silvassa - 396 230 (U.T. of D. & N.H.)

+91 99 798 54 133 gold@goldoilcorporation.com www.goldoilcorporation.com