



GOLD RUST OIL B

(Oil Base Rust Preventive)

GOLD RUST OIL B is mainly based on base oil containing a selected combination of additives that these serve as lubricants as well as temporary protectives. These products are suitable for internal protection of gear boxes, back axle assemblies, oil and fuel pumps and lines, fuel and oil tanks, i.e. engines etc

PROPERTIES:-

- Good oxidation stability and ageing resistance
- Rapid air release and low foaming
- Excellent corrosion protection.
- Avoids water spots when dewatering sensitive surfaces, such as polished or plated components.
- Good compatibility with sealing materials

GOLD RUST OIL B			
	<i>Test Properties</i>	<i>Test Method</i>	12
Specification Properties & Characteristics	Appearance	Visual	Bright & Clear
	Colour	ASTM D 1500	Light Brown
	Density @ 29.5, °C, g/ml, Min	ASTM D 1298	0.820
	Viscosity, Kinematic 40 at°C, cSt	ASTM D 445	10 - 14
	Flash Point, COC, °C, Min	ASTM D 92	150
	DEMULSIBILITY TEST	ASTM D 1401	PASS
	FILM TYPE	-	OILY & TACKY
	COPPER STRIP CORROSION 3Hrs.	ASTM D 130	1
	EVAPORATION LOSS @110°C FOR 03 HRS., % Max	ASTM D 5800	20

Packaging Options: Gold Rust Oil B is offered in 26, 50 & 210 Liter.

Health & Safety: See corresponding product MSDS

The information contained herein is, to our best knowledge, true and accurate, but all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control. There is no implied warranty of merchantability or fitness for purpose of the product or products described herein. In submitting this information, no liability is assumed or license or other rights express or implied given with respect to any existing or pending patent, patent applications or trademarks. The observance of all legal regulations and patents is the responsibility of the user.