

**GOLD RUST OIL OB 245**

GOLD RUST OIL OB 245 is mainly based on base oil containing a selected combination of additives that these serve as lubricants as well as temporary protectives. These products are suitable for internal protection of gear boxes, back axle assemblies, oil and fuel pumps and lines, fuel and oil tanks, i.e. engines etc

PROPERTIES:-

- It is a general purpose rust preventive ideal for indoor protection of machine parts is found highly acceptable.
- Good oxidation stability and ageing resistance
- Excellent corrosion protection.
- Avoids water spots when dewatering sensitive surfaces, such as polished or plated components.
- Easily can be remove film thickness.
- Good compatibility with sealing materials

GOLD RUST OIL OB 245			
	<i>Test Properties</i>	<i>Test Method</i>	<i>Specification</i>
Specification Properties & Characteristics	Appearance	Visual	Bright & Clear
	Colour	ASTM D 1500	Light Brown
	Density @ 29.5, °C, g/ml	ASTM D 1298	0.830 Min
	Viscosity, Kinematic 40 at°C, cSt	ASTM D 445	33 - 40
	Flash Point, COC, °C	ASTM D 92	200 Min
	DEMULSIBILITY TEST	ASTM D 1401	PASS
	FILM TYPE	-	OILY & TACKY
	COPPER STRIP CORROSION 3Hrs.	ASTM D 130	1

Packaging Options: GOLD RUST OIL OB 245 is offered in 26, 50 & 210 Liter.

Health & Safety: Material Safety Data Sheet can be provided on request

The information contained herein is, to our best knowledge, true and accurate, but all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control. There is no implied warranty of merchantability or fitness for purpose of the product or products described herein. In submitting this information, no liability is assumed or license or other rights express or implied given with respect to any existing or pending patent, patent applications or trademarks. The observance of all legal regulations and patents is the responsibility of the user.