



GOLD MOLY GREASE

GOLD MOLY GREASE is multipurpose grease, fortified with solid lubricant and developed for both Automotive and Industrial applications. It is based on an optimized balance of mineral base oil, lithium thickener technology and a specially selected additive system incorporating EP/anti-wear chemistry, antioxidants and corrosion inhibitors. The inclusion of molybdenum disulphide enhances load carrying performance whilst reducing friction, especially in those components where reciprocating or sliding motion is prevalent.

PROPERTIES

- Reliable High Temperature Performance
- Good Oxidation and Mechanical Stability
- The presence of molybdenum disulphide offers the benefit of reduced friction and resistance to shock loads.
- Serviceable temperature range from -18°C to $+250^{\circ}\text{C}$
- Good Corrosion Resistance Properties
- Long Storage life
- Good compatibility with sealing materials

GOLD MOLY GREASE			
Sr. No.	TEST PROPERTIES	TEST METHOD	SPECIFICATION
1.	NLGI Grade	-	3
2.	Thickener Type	-	Lithium
3.	Color	VISUAL	Gray-Black
4.	Dropping Point, Min	ASTM D 2265	190
5.	Penetration, Worked At 60 Strokes, @25°C	ASTM D 217	220 - 250
6.	4-Ball Wear, Max	ASTM D 2266	0.4
7.	4-Ball Weld Load, Kg.	ASTM D 2596	260
8.	Timken EP test, ok load in lb	ASTM D 2509	50
9.	Copper Strip Corrosion, Max	ASTM D 130	1b

Packaging Options: Gold Moly Grease is offered in 01, 05, 26, 50 & 210 Liter

Health & Safety: See corresponding product MSDS

The information contained herein is, to our best knowledge, true and accurate, but all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control. There is no implied warranty of merchantability or fitness for purpose of the product or products described herein. In submitting this information, no liability is assumed or license or other rights express or implied given with respect to any existing or pending patent, patent applications or trademarks. The observance of all legal regulations and patents is the responsibility of the user.