



GOLD SUPER TURBO 15W 40 API CH4

(Heavy Duty Engine Oil)

GOLD SUPER 15W 40 is multigrade engine oil. Viscosity grade is high quality engine oil for use in high output, turbocharged diesel engines. GOLD SUPER TURBO 15W40 is formulated to exceed API' s latest specifications: Diesel engine oil specifications: CH-4 Gasoline engine oil specification: SM, SL.

Properties

- Prolong engine life
- Superior soot control and acid neutralization.
- Protects against wear and corrosion
- Superior thermal and oxidation stability
- Reduce friction, sludge and varnish

GOLD SUPER TURBO 15W 40			
	Test Properties	Test Method	SPECIFICATION
	API SERVICE CATEGORY		CH-4/SM/SL
	SAE GRADE		15W-40
Specification & Characteristics	Appearance	Visual	Bright & Clear
	Colour	ASTM D 1500	Natural
	Density @ 29.5, °C, g/ml	ASTM D 1298	0.850 Min
	Viscosity, Kinematic 100 at°C, cSt	ASTM D 445	14 – 15
	Viscosity Index	ASTM D 2270	110 Min
	Pour Point, °C	ASTM D 97	-12 Max
	Flash Point, COC, °C	ASTM D 92	220 Min
	TBN, mg KOH/g	ASTM D 2896	8.0 Min

Packaging Options: GOLD SUPER TURBO 15W 40 CH-4 is offered in 26, 50 & 210 Liters.

Health & Safety: See corresponding product MSDS

The information contained herein is, to our best knowledge, true and accurate, but all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control. There is no implied warranty of merchantability or fitness for purpose of the product or products described herein. In submitting this information, no liability is assumed or license or other rights express or implied given with respect to any existing or pending patent, patent applications or trademarks. The observance of all legal regulations and patents is the responsibility of the user.