



GOLD SYN FLUID 5W-50

GOLD SYN FLUID 5W-50 is a fully synthetic motor oil (not for 2 cycle) using raw materials and advanced technology which guarantee complete reliability and high performance under all working conditions , including high speed highway or stop and go city driving.

Properties:-

- Excellent wear protection in all driving condition
- Prolong engine life
- Fast lubrication at extremely low temperatures making start up easy
- Superior Active Cleansing Agents help remove built-up dirt and deposits
- Superior thermal and oxidation stability
- Reduce friction, sludge and varnish

GOLD SYN FLUID 5W-50			
	Test Properties	Test Method	SPECIFICATION
	API SERVICE CATEGORY		SN/CI4
	SAE GRADE		5W-50
Specification & Characteristics	Appearance	Visual	Bright & Clear
	Colour	ASTM D 1500	Natural
	Density @ 29.5, °C, g/ml	ASTM D 1298	0.82 Min
	Viscosity, Kinematic 40 at°C, cSt	ASTM D 445	140 Max
	Viscosity, Kinematic 100 at°C, cSt	ASTM D 445	17 - 18
	Viscosity Index	ASTM D 2270	140 Min
	Pour Point, °C	ASTM D 97	-30 Max
	Flash Point, COC, °C	ASTM D 92	220 Min
TBN, mg KOH/g	ASTM D 2896	8.0 Min	

Packaging Options: GOLD SYN FLUID 5W-50 is offered in 26, 50 & 210 Liters.

Health & Safety: See corresponding product MSDS

The information contained herein is, to our best knowledge, true and accurate, but all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control. There is no implied warranty of merchantability or fitness for purpose of the product or products described herein. In submitting this information, no liability is assumed or license or other rights express or implied given with respect to any existing or pending patent, patent applications or trademarks. The observance of all legal regulations and patents is the responsibility of the user.